

Maximizing the Efficiency of Your Operation

Save both time and money utilizing Lockwood's superior separation capabilities! Use less horsepower and increase your harvesting capacity while minimizing your fleet costs.

- Right and left hand discharge to accommodate each farmer's needs
- Steerable rear wheels allow for shorter turns
- Variable speed hydraulic drive on the rear cross helps eliminate bruising
- Heavy-duty spindles, hubs and rims for longer life
- Heavy-duty trailing coulters to cut the potato vines
- Rear wheel lift for steeper angles on the primary and secondary for improved cleaning
- Digger nose available in narrow or wide
- Larger wheels for better flotation
- Available in center pull or offset hitch

Specs

Models	552, 554
Number of Rows	2, 4
Row Spacing	32" - 38"
Operating Speed	2 - 5 mph
Headland to Turn	14' - 18'
Est. HP (min)	120 - 150
Hydraulic Pressure	1500 - 2500 psi
Base Machine (lbs)	10,000, 14,000



Side Discharge

Adjustable discharge height and variable speed rear cross allows the deposit of potatoes onto the ground at a consistent, bruise-free height.



Hitch Options

Offers the flexibility to pull from the center or offset to accommodate each farmer's needs.



Rear Height Adjustment

Hydraulic rear lift allows operator to raise or lower the rear of the machine to accommodate changing conditions, even on side hills.

